

Polycarbonate IP65 Non-Corrosive LED Fittings



TECHNICAL SPECIFICATION

Single & twin rows of SMD LEDs on metal core PCB

Sizes & Order codes:

4ft Single 24W: AP-ACF1X4/840
4ft Twin 40W: AP-ACF2X4/840

5ft Single 35W: AP-ACF1X5/840
5ft Twin 57W: AP-ACF2X5/840

6ft Single 46W: AP-ACF1X6/840
6ft Twin 74W: AP-ACF2X6/840

Application: Industrial Areas, Warehouses, Garages

Construction:

- Polycarbonate base and opal diffuser
- Grade 316 stainless steel clips
- Aluminum heat sink
- Stainless steel surface mounting clips
- Can also be suspended from wire/chain using clips provided

CCT(K): 4000K - CRI >.8

Driver: Flicker free driver

Lumen Output:

4ft 24W: 2715 lm
4ft 40W: 4600 lm

5ft 35W: 3875 lm
5ft 57W: 6600 lm

6ft 46W: 5060 lm
6ft 74W: 8436 lm

Maximum Life Time: 20,000 hours

MARKS, SYMBOLS & ICONS



NOTES

- Emergency (maintained 3 hours) version available for all sizes. Add suffix /EM

*Full warranty policy details are available upon request and are also viewable on our website.