

Product Description	4ft Arrow NX NCF-power shift
----------------------------	------------------------------

Technical Specs & Notes		
Product Code	AP-SARN/4/WS/WH/840	AP-SARN/4/WS/M3/WH/ 840
Description	Arrow NX LED NCF, 1.2m, 22-38W, 3100-5000lm, 4000K, IP65	Arrow NX LED NCF, 1.2m, 22-38W, 3100-5000lm, 4000K, IP65, Emergency
Input Voltage	220-240V AC	220-240V AC
Total Wattage	22/28/32/38W	22/28/32/38W
Luminaire Lumens	3100/3800/4400/5000LM	3100/3800/4400/5000 LM
Lumens P/Watt	127lm/W	127lm/W
LED Chips	2835/102pcs	2835/102pcs
LED Forward Voltage	98V/350mA	98V/350mA
LED Chip Lifetime (L70)	50,000H	50,000H
CCT / CRI / SDCM	4000K/80/<6	4000K/80/<6
Driver	Tridonic 28004924	Tridonic 28004924
Power Factor	0.88/0.92/0.94/0.95	0.86/0.9/0.92/0.94
Running Current	98/118/139/163mA	108/129/152/176mA
Inrush Current	5.56A/47 μs	5.56A/47 μs
Sensor / PIR	NA	NA
Emergency Converter	NA	Seatronics: SL01-C550A-Li01-EL
Emergency Duration	NA	3hours
Emergency Lumens	NA	>200lm
Battery	NA	LiFePO4 3.2V 3Ah
Material / Finish (RAL)	PC base & opal PC diffuser	PC base & opal PC diffuser
Class / IP / IK	Class I/IP65/IK08	Class I/IP65/IK08
Beam Angle	115	115
Glow Wire Testing (TP rating)	850°C	850°C
Installation Method	Ceiling mounting	Ceiling mounting
Temperature	-10 to 40°C	0 to 40°C
Warranty	3 Years	3 Years(Battery 2 years)
Certificates	CE	CE

